

Managing High Availability Cluster Resources

After configuring High Availability cluster resources, you might need to start, stop, edit or delete them for various reasons. This article describes how to manage cluster resources safely.

Requirements:

- An existing SUSE Linux Enterprise High Availability cluster
- Existing cluster resources



If you still need to configure cluster resources, see [Configuring High Availability Cluster Resources](https://documentation.suse.com/sle-ha/16.0/html/HA-resources-configuring/) (<https://documentation.suse.com/sle-ha/16.0/html/HA-resources-configuring/>) [↗](#).

Publication Date: 13 Aug 2026

Contents

- 1 What are cluster resources? 3
- 2 Showing cluster resources 6
- 3 Starting cluster resources 7
- 4 Stopping cluster resources 8

5	Editing primitive resources	9
6	Editing resource groups	11
7	Cleaning up failed resources	14
8	Deleting cluster resources	15
9	Legal Notice	16
A	GNU Free Documentation License	16
	HA glossary	24

1 What are cluster resources?

In a High Availability cluster, the applications and services that need to be highly available are called *resources*. Cluster resources can include Web sites, e-mail servers, databases, file systems, virtual machines or any other applications or services that need to be available to users at all times. You can start, stop, monitor and move resources as needed. You can also specify whether resources should run together on the same node, or start and stop in sequential order. If a node fails, the resources running on it *fail over* (move) to another node instead of being lost.

In SUSE Linux Enterprise High Availability, the *cluster resource manager* (CRM) is *Pacemaker*, which manages and coordinates all cluster services. Pacemaker uses *resource agents* (RAs) to start, stop and monitor resources. A resource agent abstracts the resource and presents its status to the cluster. This means that Pacemaker only interacts with the resource agent, not with the actual application or service. SUSE Linux Enterprise High Availability supports many different resource agents that are designed to manage specific types of resources.

1.1 Primitive resources

Primitive resources represent the applications or services that need to be highly available. Configuring a primitive specifies the resource agent and any other information required for the cluster to manage a resource. To see the supported resource agent classes, run **`crm ra classes`**. To see the resource agents available within a class, run **`crm ra list CLASS`**.

Primitive resources can have the following settings:

Properties

Resource properties are the basic details required by the cluster: a unique name for the resource, and the resource agent that manages the application or service.

Parameters

Parameters are specific to each resource agent and determine the details and behavior of an application or service. To show all the parameters available for a resource agent, run **`crm ra info RESOURCE_AGENT`**.

Operations

Operations are actions that the cluster can perform on a resource, such as start, stop and monitor. To show the supported operations for a resource agent, run `crm ra info RESOURCE_AGENT` and scroll to the bottom of the output.

Meta attributes

Meta attributes change how the cluster treats a resource. To show all the meta attributes available for primitives, run `crm_resource --list-options primitive`.

Utilization attributes

If the cluster nodes have utilization attributes configured, you can add these attributes to cluster resources to help with load balancing. For more information, see https://clusterlabs.org/projects/pacemaker/doc/3.0/Pacemaker_Explained/html/utilization.html.

1.2 Resource groups

Cluster resources might depend on other resources, such as a Web server that requires an IP address and a file system. You can combine these resources into a *resource group*. Groups contain multiple primitives that need to be located together, started sequentially and stopped in the reverse order.




FIGURE 1: RESOURCE GROUP

Groups have the following properties:

Contents

Groups can only contain primitive resources, not clones or other groups.

Starting and stopping

Resources start in the order they appear and stop in the reverse order.

Location

Resources in the group must all run on the same node.

Dependency

If one of the resources can't run anywhere, then the resources that appear after it in the group can't run anywhere either.

Meta attributes

The meta attributes target-role, priority, maintenance and is-managed can be added directly to the group. All other attributes are inherited from the group's resources.

Resource stickiness

Stickiness in groups is additive. Every *active* resource in the group contributes its stickiness value to the group's total.

1.3 Resource clones

Resource clones can run simultaneously on multiple nodes. This is required for cluster file systems like GFS2, for example. You can clone a primitive or a group if the resource agent supports it. Clones can also have additional clone-specific meta attributes to change their behavior.

Clones can be one of the following types:

Anonymous clones

Anonymous clones are the simplest type. All instances of the clone behave identically. Therefore, only one instance of an anonymous clone can be active on each node.

Globally unique clones

Globally unique clones are distinct entities. An instance of the clone running on one node is not necessarily equivalent to another instance on another node.

Promotable clones

Promotable clones allow the instances to be in one of two operating modes: promoted or unpromoted (also known as primary and secondary, or active and passive). Promotable clones can be either anonymous or globally unique.

To make a clone promotable, the resource agent must support the *promote* and *demote* operations. The cluster determines which instance of the clone to promote using one of the following methods (or a combination of both):

- If a resource agent supports promotable clones, it might automatically set promotion scores based on its own preference for which instance to promote.
- You can manually set promotion rules or preferences by creating location or colocation constraints.

For more information, see https://clusterlabs.org/projects/pacemaker/doc/3.0/Pacemaker_Explained/html/collective.html#determining-which-instance-is-promoted ↗

1.4 For more information

- Primitive resources: https://clusterlabs.org/projects/pacemaker/doc/3.0/Pacemaker_Explained/html/resources.html ↗
- Groups and clones: https://clusterlabs.org/projects/pacemaker/doc/3.0/Pacemaker_Explained/html/collective.html ↗
- Resource operations: https://clusterlabs.org/projects/pacemaker/doc/3.0/Pacemaker_Explained/html/operations.html ↗
- Utilization attributes: https://clusterlabs.org/projects/pacemaker/doc/3.0/Pacemaker_Explained/html/utilization.html ↗

2 Showing cluster resources

You can check the status and configuration of existing cluster resources with the CRM Shell (`crmsh`) or with the Hawk Web interface.

CRM Shell

You can perform this procedure on any node in the cluster.

1. Log in either as the `root` user or as a user with `sudo` privileges.
2. Show the status of the resources:

```
> sudo crm resource status
```

3. Show the configuration of the resources. The basic command shows the full CIB:

```
> sudo crm configure show
```

You can limit the output by using modifiers such as an object's name, type or tag. For more information about the available modifiers, run the following command:

```
> sudo crm configure help show
```

Hawk

You can use Hawk on any machine with a Web browser and network access to the nodes.

1. In a Web browser, go to <https://HAWKSERVER:7630/> and log in.

The *Status* page shows the cluster resources and their statuses. If the resource is a group or a clone, you can click the plus icon to show the child resources.

2. From the left navigation bar, select *Configuration* > *Edit Configuration*.

On this page, you can click different tabs to view more details about cluster objects such as resources, constraints or nodes. You can also limit the results by using the *Search* bar.

3. To view the full CIB, click *Show*.

Alternatively, you can click *XML* to view the XML representation of the CIB.

3 Starting cluster resources

You can start cluster resources with the CRM Shell (`crmsh`) or with the Hawk Web interface.

REQUIREMENTS

- The application or service that the cluster resource manages must be set up correctly. For example, if you have a resource managing an Apache server, the Apache configuration must be complete before you start the resource, or the start action will fail.

CRM Shell

You can perform this procedure on any node in the cluster.

1. Log in either as the `root` user or as a user with `sudo` privileges.
2. Check the current status of the resource:

```
> sudo crm resource status
```

3. Start the resource. If necessary, you can start multiple resources at once:

```
> sudo crm resource start RESOURCE1 RESOURCE2
```

4. Check the status again to make sure the resource started successfully:

```
> sudo crm resource status
```

Hawk

You can use Hawk on any machine with a Web browser and network access to the nodes.

1. In a Web browser, go to <https://HAWKSERVER:7630/> and log in.
2. From the left navigation bar, select *Monitoring > Status*.
The *Resources* tab shows the *Status* of the cluster resources. A stopped resource has a red *Status* icon and an empty *Location* column.
3. Find the resource you want to start. In its *Operations* column, click the *Start* icon.
4. Click *OK* to continue.
The resource's *Status* icon changes to green, and the *Location* column shows which node the resource is running on.

4 Stopping cluster resources

You can stop cluster resources with the CRM Shell (`crmsh`) or with the Hawk Web interface.

CRM Shell

You can perform this procedure on any node in the cluster.

1. Log in either as the `root` user or as a user with `sudo` privileges.
2. Check the current status of the resource:

```
> sudo crm resource status
```

3. Stop the resource. If necessary, you can stop multiple resources at once:

```
> sudo crm resource stop RESOURCE1 RESOURCE2
```

4. Check the status again to make sure the resource stopped successfully:

```
> sudo crm resource status
```

Hawk

You can use Hawk on any machine with a Web browser and network access to the nodes.

1. In a Web browser, go to `https://HAWKSERVER:7630/` and log in.
2. From the left navigation bar, select *Monitoring > Status*.
The *Resources* tab shows the *Status* of the cluster resources. A running resource has a green *Status* icon.
3. Find the resource you want to stop. In its *Operations* column, click the *Stop* icon.
4. Click *OK* to continue.
The resource's *Status* icon changes to red.

5 Editing primitive resources

You can edit primitive resources with the CRM Shell (`crmsch`) or with the Hawk Web interface.

CRM Shell

You can perform this procedure on any node in the cluster.

1. Log in either as the `root` user or as a user with `sudo` privileges.
2. To add a new monitor operation, use the following command:

```
> sudo crm configure monitor RESOURCE INTERVAL:TIMEOUT
```

3. To add a new parameter, meta attribute or utilization attribute, use one of the following commands:

```
> sudo crm resource param RESOURCE set PARAMETER VALUE
> sudo crm resource meta RESOURCE set ATTRIBUTE VALUE
> sudo crm resource utilization RESOURCE set ATTRIBUTE VALUE
```

4. To delete a parameter, meta attribute or utilization attribute, use one of the following commands:

```
> sudo crm resource param RESOURCE delete PARAMETER
> sudo crm resource meta RESOURCE delete ATTRIBUTE
> sudo crm resource utilization RESOURCE delete ATTRIBUTE
```

5. To change multiple attributes at once, use the following command:

```
> sudo crm configure edit RESOURCE
```

This command opens the CIB representation of the resource in a text editor. You can make multiple changes to the resource's configuration, then save and exit.



Don't use this command to rename a resource. The change won't apply to related objects.

6. To rename a resource, first stop the resource, then use the following command:

```
> sudo crm configure rename OLD_NAME NEW_NAME
```

This also changes the resource's name in related objects such as constraints, groups and clones.

Hawk

You can use Hawk on any machine with a Web browser and network access to the nodes.

1. In a Web browser, go to <https://HAWKSERVER:7630/> and log in.
2. From the left navigation bar, select *Configuration* > *Edit Configuration*.
3. Find the resource you want to edit. In the *Operations* column, click the *Edit* icon.

4. At the top of the configuration screen, you can select the following operations:
 - *Copy* the resource.
 - *Rename* the resource. The resource must be stopped before you perform this operation.
 - *Delete* the resource.
5. To add a new parameter, operation or meta attribute, select an item from one of the drop-down lists.
6. To delete a parameter, operation or meta attribute, click the minus icon.
7. To edit an existing parameter, enter a new value in the text field.
8. To edit an existing meta attribute, select a new value from the drop-down list.
9. To edit an existing operation, click the *Edit* icon.

A new window opens. Enter a different value or add a new attribute, then click *Apply* to close the window.
10. If you make a mistake, you can click *Revert* to undo your changes. This option is only available *before* you confirm the changes.
11. Click *Apply* to confirm the changes.

A message at the top of the screen shows if the action was successful.

FOR MORE INFORMATION

- [crm configure help edit](#)
- [crm configure help monitor](#)
- [crm configure help rename](#)
- [crm resource help meta](#)
- [crm resource help param](#)
- [crm resource help util](#)

6 Editing resource groups

You can edit resource groups with the CRM Shell (`crmsh`) or with the Hawk Web interface.

CRM Shell

You can perform this procedure on any node in the cluster.

1. Log in either as the `root` user or as a user with `sudo` privileges.
2. To remove a resource from a group, use the following command:

```
> sudo crm configure modgroup GROUP remove RESOURCE
```

3. To add a resource to a group, use the following command:

```
> sudo crm configure modgroup GROUP add RESOURCE
```

The resource is appended to the end of the group, meaning it starts last and stops first.

Alternatively, you can use `before` or `after` to add the resource to a specific position in the group's order:

```
> sudo crm configure modgroup GROUP add RESOURCE0 before RESOURCE1
```

```
> sudo crm configure modgroup GROUP add RESOURCE2 after RESOURCE1
```

4. To change the order of resources that are already in the group, use the following command:

```
> sudo crm configure edit GROUP
```

This command opens the CIB representation of the group in a text editor. You can make multiple changes to the group's configuration, then save and exit.



Don't use this command to rename a group. The change won't apply to related objects.

5. To rename a group, use the following command:

```
> sudo crm configure rename OLD_NAME NEW_NAME
```

This also changes the group's name in related objects such as constraints and clones.

Hawk

You can use Hawk on any machine with a Web browser and network access to the nodes.

1. In a Web browser, go to <https://HAWKSERVER:7630/> and log in.
2. From the left navigation bar, select *Configuration > Edit Configuration*.

3. Find the group you want to edit. In the *Operations* column, click the *Edit* icon.
4. At the top of the configuration screen, you can select the following operations:
 - *Create* a new group.
 - *Rename* the group.
 - *Delete* the group.
5. In the list of *Children*, you can make the following changes:
 - Add resources to the group.
 - Remove resources from the group.
 - Drag and drop resources into a different order using the icons on the right.
6. To add a new meta attribute, select an item from the drop-down list.
7. To delete a meta attribute, click the minus icon.
8. To edit an existing meta attribute, select a new value from the drop-down list.
9. If you make a mistake, you can click *Revert* to undo your changes. This option is only available *before* you confirm the changes.
10. Click *Apply* to confirm the changes.

A message at the top of the screen shows if the action was successful.

FOR MORE INFORMATION

- [crm configure help edit](#)
- [crm configure help modgroup](#)
- [crm configure help rename](#)

7 Cleaning up failed resources

The cluster automatically restarts resources if they fail, but each failure increases the resource's *fail count*. If the fail count reaches the resource's *migration threshold*, the current node becomes ineligible to run the resource. The cluster either moves the resource to an eligible node or stops the resource if no eligible node is available.

By default, fail counts are not automatically reset. This procedure explains how to reset the fail count manually.

You can clean up failed resources with the CRM Shell (`crmsh`) or with the Hawk Web interface. If the resource is part of a group, the other resources in the group are also cleaned up.

CRM Shell

You can perform this procedure on any node in the cluster.

1. Log in either as the `root` user or as a user with `sudo` privileges.
2. Show the status of the cluster, including fail counts:

```
> sudo crm status failcounts
```

If a resource has a fail count, it appears in the Migration Summary section.

3. Clean up the resource on all nodes:

```
> sudo crm resource cleanup RESOURCE
```

Alternatively, you can clean up the resource on a specific node:

```
> sudo crm resource cleanup RESOURCE NODE
```

Hawk

You can use Hawk on any machine with a Web browser and network access to the nodes.

1. In a Web browser, go to <https://HAWKSERVER:7630/> and log in.
2. From the left navigation bar, select *Monitoring* > *Status*.
3. Find the resource you want to clean up. In its *Operations* column, click the down arrow icon and select *Cleanup*.

4. From the drop-down list, either keep the default *Clean up on all nodes* or select a specific node.
5. Click *OK* to continue.
A message at the top of the screen shows if the action was successful.



Tip: Automatically resetting fail counts

You can configure a cluster resource's fail count to reset automatically by adding the `failure-timeout` meta attribute to the resource.

FOR MORE INFORMATION

- [crm resource help cleanup](#)

8 Deleting cluster resources

You can delete a resource from the cluster configuration with the CRM Shell (`crmsh`) or with the Hawk Web interface.

REQUIREMENTS

- If the resource has the status `FAILED`, you must clean it up before you can delete it.

CRM Shell

You can perform this procedure on any node in the cluster.

1. Log in either as the `root` user or as a user with `sudo` privileges.
2. Check the current status of the resource:

```
> sudo crm resource status
```

3. If the resource is `Started`, you can stop it with the following command:

```
> sudo crm resource stop RESOURCE
```

4. Delete the resource. If necessary, you can delete multiple resources at once:

```
> sudo crm configure delete RESOURCE1 RESOURCE2
```

Hawk

You can use Hawk on any machine with a Web browser and network access to the nodes.

1. In a Web browser, go to <https://HAWKSERVER:7630/> and log in.
2. From the left navigation bar, select *Configuration* › *Edit Configuration*.
3. Find the resource you want to delete. In its *Operations* column, click the *Delete* icon.
When using Hawk, you don't need to stop the resource before deleting it.
4. Click *OK* to continue.
A message at the top of the screen shows if the action was successful.

FOR MORE INFORMATION

- [crm configure help delete](#)

9 Legal Notice

Copyright© 2006– 2026 SUSE LLC and contributors. All rights reserved.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or (at your option) version 1.3; with the Invariant Section being this copyright notice and license. A copy of the license version 1.2 is included in the section entitled “GNU Free Documentation License”.

For SUSE trademarks, see <https://www.suse.com/company/legal/> . All other third-party trademarks are the property of their respective owners. Trademark symbols (®, ™ etc.) denote trademarks of SUSE and its affiliates. Asterisks (*) denote third-party trademarks.

All information found in this book has been compiled with utmost attention to detail. However, this does not guarantee complete accuracy. Neither SUSE LLC, its affiliates, the authors, nor the translators shall be held liable for possible errors or the consequences thereof.

A GNU Free Documentation License

Copyright (C) 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or non-commercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retile any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <https://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

Copyright (c) YEAR YOUR NAME.

```
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
A copy of the license is included in the section entitled "GNU
Free Documentation License".
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

HA glossary

active/active, active/passive

How resources run on the nodes. Active/passive means that resources only run on the active node, but can move to the passive node if the active node fails. Active/active means that all nodes are active at once, and resources can run on (and move to) any node in the cluster.

arbitrator

An *arbitrator* is a machine running outside the cluster to provide an additional instance for cluster calculations. For example, *QNetd* provides a vote to help *QDevice* participate in *quorum* decisions.

CIB (cluster information base)

An XML representation of the whole cluster configuration and status (cluster options, nodes, resources, constraints, etc.). The CIB manager (pacemaker - based) keeps the CIB synchronized across the cluster nodes and handles requests to modify it.

clone

In the context of a cluster *resource*, a clone is a resource that can be active on multiple nodes. Any resource can be cloned if its resource agent supports it.

cluster

A *high-availability* cluster is a group of servers (physical or virtual) designed primarily to secure the highest possible availability of data, applications and services. Not to be confused with a *high-performance* cluster, which shares the application load to achieve faster results.

Cluster LVM (Cluster logical volume manager)

The term *Cluster LVM* indicates that LVM is being used in a cluster environment. This requires configuration adjustments to protect the LVM metadata on shared storage.

cluster offline upgrade

If a new product version includes major changes that are backward incompatible, the cluster requires a cluster offline upgrade. You must stop the cluster services on all nodes and upgrade the whole cluster before bringing the nodes back online.

For minor version upgrades, see [cluster rolling upgrade](#).

cluster partition

A cluster partition occurs when communication fails between one or more nodes and the rest of the cluster. The nodes are split into partitions but are still active. They can only communicate with nodes in the same partition and are unaware of the separated nodes. This is known as a *split brain* scenario.

cluster rolling upgrade

In a cluster rolling upgrade, one cluster node at a time is upgraded while the rest of the cluster is still running. Stop the cluster services on a node, upgrade it, then bring it back online to join the cluster. Continue one by one until all cluster nodes are upgraded.

For major version upgrades, see [cluster offline upgrade](#).

cluster services

The services that run the cluster. Typically this refers to Pacemaker and Corosync, but might also include SBD and QDevice if those services are used.

cluster stack

The ensemble of software technologies and components that make up a cluster.

colocation constraint

A type of *resource constraint* that specifies which resources can or cannot run together on a node.

concurrency violation

A resource that should be running on only one node in the cluster is running on several nodes.

Corosync

Corosync provides reliable messaging, membership and quorum information about the cluster. This is handled by the Corosync Cluster Engine, a group communication system.

CRM (cluster resource manager)

The management entity responsible for coordinating all non-local interactions in a High Availability cluster. SUSE Linux Enterprise High Availability uses *Pacemaker* as the CRM. It interacts with several components: local executors on its own node and on the other nodes, non-local CRMs, administrative commands, the fencing functionality, and the membership layer.

crmsh (CRM Shell)

The command-line utility crmsh manages the cluster, nodes and resources.

Csync2

A synchronization tool for replicating configuration files across all nodes in the cluster.

DC (designated coordinator)

The pacemaker - control d daemon is the cluster controller, which coordinates all actions. This daemon has an instance on each cluster node, but only one instance is elected to act as the DC. The DC is elected when the cluster services start, or if the current DC fails or leaves the cluster. The DC decides whether a cluster-wide change must be performed, such as fencing a node or moving resources.

disaster

An unexpected interruption of critical infrastructure caused by nature, humans, hardware failure, or software bugs.

disaster recovery

The process by which a function is restored to the normal, steady state after a disaster.

Disaster Recovery Plan

A strategy to recover from a disaster with the minimum impact on IT infrastructure.

DLM (Distributed Lock Manager)

DLM coordinates accesses to shared resources in a cluster, for example, managing file locking in clustered file systems to increase performance and availability.

DRBD

DRBD® is a block device designed for building High Availability clusters. It replicates data on a primary device to secondary devices in a way that ensures all copies of the data remain identical.

existing cluster

The term *existing cluster* is used to refer to any cluster that consists of at least one node. An existing cluster has a basic *Corosync* configuration that defines the communication channels, but does not necessarily have resource configuration yet.

failover

Occurs when a resource or node fails on one machine and the affected resources move to another node.

failover domain

A named subset of cluster nodes that are eligible to run a resource if a node fails.

fencing

Prevents access to a shared resource by isolated or failing cluster members. There are two classes of fencing: *resource-level* fencing and *node-level* fencing. Resource-level fencing ensures exclusive access to a resource. Node-level fencing prevents a failed node from accessing shared resources and prevents resources from running on a node with an uncertain status. This is usually done by resetting or powering off the node.

GFS2

Global File System 2 (GFS2) is a shared disk file system for Linux computer clusters. GFS2 allows all nodes to have direct concurrent access to the same shared block storage. GFS2 has no disconnected operating mode, and no client or server roles. All nodes in a GFS2 cluster function as peers. GFS2 supports up to 32 cluster nodes. Using GFS2 in a cluster requires hardware to allow access to the shared storage, and a lock manager to control access to the storage.

group

Resource groups contain multiple resources that need to be located together, started sequentially and stopped in the reverse order.

Hawk (HA Web Konsole)

A user-friendly Web-based interface for monitoring and administering a High Availability cluster from Linux or non-Linux machines. Hawk can be accessed from any machine that can connect to the cluster nodes, using a graphical Web browser.

heuristics

QDevice supports using a set of commands (*heuristics*) that run locally on start-up of cluster services, cluster membership change, successful connection to the *QNetd* server, or optionally at regular times. The result is used in calculations to determine which partition should have *quorum*.

knet (kronosnet)

A network abstraction layer supporting redundancy, security, fault tolerance, and fast fail-over of network links. In SUSE Linux Enterprise High Availability 16, *knet* is the default transport protocol for the *Corosync* communication channels.

local cluster

A single cluster in one location (for example, all nodes are located in one data center). Network latency is minimal. Storage is typically accessed synchronously by all nodes.

local executor

The local executor is located between *Pacemaker* and the resources on each node. Through the pace-maker-execd daemon, Pacemaker can start, stop and monitor resources.

location

In the context of a whole cluster, *location* can refer to the physical location of nodes (for example, all nodes might be located in the same data center). In the context of a *location constraint*, *location* refers to the nodes on which a resource can or cannot run.

location constraint

A type of *resource constraint* that defines the nodes on which a resource can or cannot run.

meta attribute

Parameters that tell the *CRM (cluster resource manager)* how to treat a specific *resource*. For example, you might define a resource's priority or target role.

metro cluster

A single cluster that can stretch over multiple buildings or data centers, with all sites connected by Fibre Channel. Network latency is usually low. Storage is frequently replicated using mirroring or synchronous replication.

network device bonding

Network device bonding combines two or more network interfaces into a single bonded device to increase bandwidth and/or provide redundancy. When using *Corosync*, the bonded device is not managed by the cluster software. Therefore, the bonded device must be configured on every cluster node that might need to access it.

node

Any server (physical or virtual) that is a member of a cluster.

order constraint

A type of *resource constraint* that defines the sequence of actions.

Pacemaker

Pacemaker is the *CRM (cluster resource manager)* in SUSE Linux Enterprise High Availability, or the “brain” that reacts to events occurring in the cluster. Events might be nodes that join or leave the cluster, failure of resources, or scheduled activities such as maintenance, for example. The pacemakerd daemon launches and monitors all other related daemons.

parameters (instance attributes)

Parameters determine which instance of a service the *resource* controls.

primitive

A primitive resource is the most basic type of cluster resource.

promotable clone

Promotable clones are a special type of *clone* resource that can be promoted. Active instances of these resources are divided into two states: promoted and unpromoted (also known as “active and passive” or “primary and secondary”).

QDevice

QDevice and *QNetd* participate in *quorum* decisions. The corosync-qdevice daemon runs on each cluster node and communicates with QNetd to provide a configurable number of votes, allowing a cluster to sustain more node failures than the standard quorum rules allow.

QNetd

QNetd is an *arbitrator* that runs outside the cluster. The corosync-qnetd daemon provides a vote to the corosync-qdevice daemon on each node to help it participate in quorum decisions.

quorum

A *cluster partition* is defined to have quorum (be *quorate*) if it has the majority of nodes (or “votes”). Quorum distinguishes exactly one partition. This is part of the algorithm to prevent several disconnected partitions or nodes (“split brain”) from proceeding and causing data and service corruption. Quorum is a prerequisite for fencing, which then ensures that quorum is unique.

RA (resource agent)

A script acting as a proxy to manage a *resource* (for example, to start, stop or monitor a resource). SUSE Linux Enterprise High Availability supports different kinds of resource agents.

ReaR (Relax and Recover)

An administrator tool set for creating *disaster recovery* images.

resource

Any type of service or application that is known to *Pacemaker*, for example, an IP address, a file system, or a database. The term *resource* is also used for *DRBD*, where it names a set of block devices that use a common connection for replication.

resource constraint

Resource constraints specify which cluster nodes a resource can run on, what order the resources should start in, and which other resources a specific resource is dependent on.

See also *colocation constraint*, *location constraint* and *order constraint*.

resource set

As an alternative format for defining location, colocation or order constraints, you can use *resource sets*, where primitives are grouped together in one set. When creating a constraint, you can specify multiple resources for the constraint to apply to.

resource template

To help create many resources with similar configurations, you can define a resource template. After being defined, it can be referenced in primitives or in certain types of constraints. If a template is referenced in a primitive, the primitive inherits all operations, instance attributes (parameters), meta attributes and utilization attributes defined in the template.

SBD (STONITH Block Device)

SBD provides a node *fencing* mechanism through the exchange of messages via shared block storage. Alternatively, it can be used in diskless mode. In either case, it needs a hardware or software *watchdog* on each node to ensure that misbehaving nodes are really stopped.

scheduler

The scheduler is implemented as *pacemaker-schedulerd*. When a cluster transition is needed, *pacemaker-schedulerd* calculates the expected next state of the cluster and determines what actions need to be scheduled to achieve the next state.

split brain

A scenario in which the cluster nodes are divided into two or more groups that do not know about each other (either through a software or hardware failure). *STONITH* prevents a split-brain scenario from badly affecting the entire cluster. Also known as a *partitioned cluster* scenario.

The term *split brain* is also used in *DRBD* but means that the nodes contain different data.

SPOF (single point of failure)

Any component of a cluster that, if it fails, triggers the failure of the entire cluster.

stickiness

Resource stickiness is a *meta attribute* that determines how much a resource prefers to stay on its current node.

STONITH

Another term for the *fencing* mechanism that shuts down a misbehaving node to prevent it from causing trouble in a cluster. In a *Pacemaker* cluster, node fencing is managed by the fencing subsystem pacemaker-fenced.

switchover

The planned moving of resources to other nodes in a cluster. See also *failover*.

utilization

Tells the CRM what capacity a certain *resource* requires from a node.

watchdog

SBD (STONITH Block Device) needs a watchdog on each node to ensure that misbehaving nodes are really stopped. SBD “feeds” the watchdog by regularly writing a service pulse to it. If SBD stops feeding the watchdog, the hardware enforces a system restart. This protects against failures of the SBD process itself, such as becoming stuck on an I/O error.