Introduction to SLES Minimal VM

SLES Minimal VM images allow you to run SUSE Linux Enterprise Server in a virtual or cloud environment without having to perform a full installation. Learn which Minimal VM image to choose, the ways to deploy them and how to configure them on first boot.

Publication Date: 05 Nov 2026

Contents

1 What is SLES Minimal VM? 2

2 Differences between SLES Minimal VM and SUSE Linux Enterprise Server 4

3 Obtaining Minimal VM images 5

4 Interactive setup with JeOS Firstboot 5

5 Automated setup using Combustion 7

6 Deploying an image with `cloud-init` 9

7 Post-deployment configuration 14

8 Legal Notice 15

A GNU Free Documentation License 16

1 What is SLES Minimal VM?

SLES Minimal VM is a set of ready-to-run virtual machine images that let you deploy SUSE Linux Enterprise Server without running an installer. Each image includes a lightweight system, serving as a foundation for building systems for use in a data center, creating virtual application images and building appliances. Because the images contain fewer packages, they require less patching and expose fewer potential security vulnerabilities.

1.1 Deployment options

SLES Minimal VM is available as preconfigured and ready-to-run virtual machine images. It is also possible to create customized Minimal VM images using the supplied KIWI NG configuration files, called templates. They are provided by the `kiwi-templates-Minimal` package. For more information about how to use KIWI templates, see KIWI NG Documentation (https://documentation.suse.com/appliance/kiwi-9/).

1.2 Default configuration

The following settings are active as soon as a Minimal VM image boots. They describe the state of the system as shipped. For how Minimal VM differs from an installed SUSE Linux Enterprise Server system, see *Section 2, "Differences between SLES Minimal VM and SUSE Linux Enterprise Server"*.

First-boot provisioning

For an automated setup, you can use Combustion to configure the system on first boot from a configuration you supply. Alternatively, on cloud and VMware images, you can use `cloud-init`. If no configuration is provided, the JeOS Firstboot wizard runs on first boot and allows you to configure basic settings, such as system locales and the `root` password.

Note: Exception for IBM Z

On s390x flavors targeting z/VM (such as DASD and FCP), the JeOS Firstboot wizard is not supported due to terminal limitations. On these images, **`systemd-firstboot`** is used instead.

Access and remote authentication

SSH on TCP port 22 is enabled as the default externally accessible port. Remote password-based `root` login is disabled by default.

- `cloud-init` and Combustion can be used to create a user account and install SSH public keys supplied in the configuration.
- When using JeOS Firstboot, the wizard prompts you to set a local `root` password, create a standard user account and enroll SSH public keys for remote access.

Networking

The default network configuration uses DHCP, managed by NetworkManager.

Security and firewall

The Minimal VM sets SELinux to enforcing mode by default. The status of the host-based firewall depends on the image you deploy:

- On the cloud image, no firewall service is installed or enabled.
- On the non-cloud images, the `firewalld` package is installed and the service is enabled and running by default.

Kernel

SLES Minimal VM images use the `kernel-default-base` as the default kernel, which contains only a subset of kernel modules. This results in a smaller image size.

System recovery

On the non-cloud images, the system automatically creates a Btrfs snapshot including the initial configuration. This means that you can easily revert all subsequent changes, if necessary.

Core dumps

Unlike in previous versions, `systemd-coredump` is enabled by default in SLES Minimal VM 16.0 to collect application core dumps for troubleshooting.

System registration

The Minimal VM images contain no preconfigured software repositories. Register the system to access online repositories. Registration requires a paid subscription.

2 Differences between SLES Minimal VM and SUSE Linux Enterprise Server

The following differences affect how you deploy and operate the system:

No installation step

There is no installer to run. The images are ready to boot, and basic settings are configured on first boot using the JeOS Firstboot tool, Combustion or `cloud-init`.

Reduced kernel

To keep the image small, Minimal VM uses `kernel-default-base` as the default kernel. This kernel does not contain drivers for bare metal. If your scenario requires additional drivers, install the `kernel-default` package to get the full functionality. This is the kernel used by a regular installation.

Zypper configuration

Part of the size reduction comes from two options in the Zypper configuration:

- `rpm.install.excludedocs = yes` excludes all files marked as documentation, such as man pages, from installation.
- `solver.onlyRequires = true` disables installation of supplementing and recommended packages.

Base packages

The images are built from KIWI NG templates that list the packages to include. Keep in mind that packages listed in a template can pull in dependencies during the build, so an image usually contains more packages than the template names.

Predefined disk layout

Unlike SUSE Linux Enterprise Server, which calculates an adjustable disk layout proposal during installation, SLES Minimal VM uses a predefined virtual image partitioning scheme:

- 2 MB BIOS boot
- 512 MB EFI system

- 24 GB root file system in non-cloud flavors
- A dynamically sized root file system in cloud flavors

To add space, either extend the existing disk from the virtual host or add a secondary disk to the virtual machine. If you extend the existing disk, the `kiwi-repart` dracut module automatically resizes the root partition and its file system to fill the available space during the next boot. If you add a secondary disk, you must partition and format it manually.

3 Obtaining Minimal VM images

The image you choose determines the hypervisor you can run it on and how the system is configured on first boot. The initial configuration mechanism depends on your target environment.

Download the images from the official Download (https://www.suse.com/download/sles/) page. Images have the platform in the name, based on their purpose:

- `Cloud` for cloud platforms
- `kvm-and-xen` for KVM and Xen hypervisors
- `MS-HyperV` for Microsoft Hyper-V hypervisors
- `VMware` for VMware hypervisors

Note: Architecture-specific naming

Depending on the architecture, image names might instead indicate specific hardware, storage types or disk formats.

4 Interactive setup with JeOS Firstboot

By default, if you boot the virtual machine without providing an automated configuration method (such as Combustion or `cloud-init`), the system launches JeOS Firstboot. To deploy the image interactively, manually complete this text-based wizard on the system console. Deploying involves two tasks:

1. Start the virtual machine on your platform.
2. Configure the system on the first boot with JeOS Firstboot.

Note: Exception for IBM Z

On s390x flavors targeting z/VM (such as DASD and FCP), the JeOS Firstboot wizard is not supported due to terminal limitations. On these images, **`systemd-firstboot`** is used instead.

Because starting a virtual machine varies wildly by platform, the exact procedure depends on your hypervisor. For platforms such as Microsoft Hyper-V and VMware, use their respective management tools to create the virtual machine.

4.1 Starting a KVM virtual machine

For KVM-compatible images, you can start the virtual machine directly by using QEMU or **`virt-install`**.

QEMU:

```
> qemu-system-ARCH \
    -enable-kvm \
    -cpu host \
    -m 1G \
    -smp 1 \
    -drive if=virtio,format=qcow2,file=IMAGE.qcow2 \
    -nographic \
    -netdev user,id=net0,hostfwd=tcp::2222-:22 \
    -device virtio-net,netdev=net0
```

`virt-install`:

```
> virt-install \
    --name VM_NAME \
    --memory 1024 \
    --vcpus 1 \
    --import \
    --disk IMAGE.qcow2,bus=virtio \
    --osinfo detect=on,require=off
```

4.2 Configuring a system with JeOS Firstboot

JeOS Firstboot is a text-based wizard that runs on the first boot and collects the basic settings. It appears on the console of the virtual machine, whichever platform you started it on.

1. Select the keyboard layout.
2. Read and accept the license agreement. You cannot proceed without accepting it.
3. Select the time zone.
4. Enter and confirm the `root` password.
5. Optionally, enroll keys for SSH access and create additional user accounts.
6. After the first boot, register the system. For more information, see *Section 7, "Post-deployment configuration"*. If you are only testing the image, you can skip registration.

Tip: Reconfiguring settings with `jeos-config`

If you need to change these settings after the initial deployment, you can use **`jeos-config`**. Running this command as `root` opens an interactive text-based tool where you can adjust your initial choices.

5 Automated setup using Combustion

SLES Minimal VM comes with the Combustion configuration tool, which configures the system on first boot from a script that you supply. This can be particularly useful when you need to deploy multiple virtual machines with an identical initial configuration. When Combustion runs successfully, JeOS Firstboot does not start. Because Minimal VM does not configure a default `root` password, the script must include a login method, either a `root` password or an SSH public key for remote access.

1. Create a configuration file named `script`.
   For more information about how to create the script, see https://documentation.suse.com/sle-micro/html/Micro-deployment-raw-images-virtual-machines/index.html#configuring-combustion-script.
2. Add at least one login method to the script:
   - To log in with a password, generate a hash of your desired `root` password:

     ```
     > openssl passwd -6
     ```

Add the following line to the script, replacing *HASH* with the value you just generated:

```
echo 'root:HASH' | chpasswd -e
```

- To set up SSH key authentication, add the following lines to the script:

```
mkdir -pm 700 /root/.ssh
echo 'SSH_PUBLIC_KEY' >> /root/.ssh/authorized_keys
```

3. Make the script executable:

```
> chmod +x script
```

4. Pass the script to the virtual machine. Use the method that matches your platform.

KVM platforms

Pass the script file directly with `fw_cfg`.

QEMU:

```
> qemu-system-ARCH \
    -enable-kvm \
    -cpu host \
    -m 1G \
    -smp 1 \
    -drive if=virtio,format=qcow2,file=IMAGE.qcow2 \
    -nographic \
    -netdev user,id=net0,hostfwd=tcp::2222-:22 \
    -device virtio-net,netdev=net0 \
    -fw_cfg name=opt/org.opensuse.combustion/script,file=script
```

`virt-install`:

```
> virt-install \
    --name VM_NAME \
    --memory 1024 \
    --vcpus 1 \
    --import \
    --disk IMAGE.qcow2,bus=virtio \
    --osinfo detect=on,require=off \
    --sysinfo type=fwcfg,entry0.name="opt/org.opensuse.combustion/
script",entry0.file="ABSOLUTE_PATH_TO_SCRIPT"
```

Microsoft Hyper-V, VMware and other platforms

Provide the script on a storage device with the file system label `combustion`, holding the script at `combustion/script`.

To build such a device as an ISO image:

```
> mkdir -p iso_root/combustion
> mv script iso_root/combustion/
> mkisofs -output combustion.iso -volid combustion -rational-rock iso_root
```

Create the virtual machine using your downloaded Minimal VM image as the primary virtual hard disk. Before booting the virtual machine for the first time, attach `combustion.iso` as a virtual disc drive.

By default, Combustion produces no output while it runs. The indication that it worked is that JeOS Firstboot does not start and you can log in as `root` using the method you configured in the script.

6 Deploying an image with `cloud-init`

The cloud and VMware Minimal VM images can use `cloud-init` to configure the system on first boot from a `user-data` file. Deploying with `cloud-init` has two parts: writing the configuration and making it available to the virtual machine through a data source.

If no data source is provided, the system defaults to JeOS Firstboot on initial boot.

Note: Scope of the `cloud-init` section

This section applies to images on a local hypervisor, where `cloud-init` uses the `NoCloud` data source.

On VMware and on cloud platforms such as OpenStack, supply your `user-data` through the interface of the platform. For the data sources that `cloud-init` supports, see https://docs.cloud-init.io/en/latest/reference/datasources.html#datasources-supported.

6.1 How to write the `user-data` file

To deploy the image with `cloud-init`, you must first create the `user-data` file. The first line of the file must be `#cloud-config`.

To view the default SUSE configuration for `cloud-init`, check the `/etc/cloud/cloud.cfg` file provided by the `cloud-init-config-suse` package.

By default, `cloud-init` does not set a `root` password. Instead, it creates a user account called `sles` that acts as the default user and has **`sudo`** rights. Use the following example to create passwords for both users.

EXAMPLE 1: ADD PASSWORDS

```
#cloud-config
chpasswd:
  list: |
    root:$6$HdJCmMKHZT2NLcwv
$4cRJ4yGGmDpPIvt0pqSa3KeEOKMKT8vR4DrYX23LlYrvM6suF79CzWomCFyreiT645fWVaFXMtyUM5zFOJMa9/
    sles:$6$HdJCmMKHZT2NLcwv
$4cRJ4yGGmDpPIvt0pqSa3KeEOKMKT8vR4DrYX23LlYrvM6suF79CzWomCFyreiT645fWVaFXMtyUM5zFOJMa9/
  expire: False
```

To create the SHA-512 hashes used in the example, run the command: **`openssl passwd -6`**.

Warning: User passwords

To prevent potential security risks, avoid using passwords in production environments. When using hashed passwords, you are exposed to dictionary attacks. For better security, use SSH authentication instead.

However, local logins, for example, in a recovery scenario, still require a password. This is why setting a `root` password, as shown in the previous example, might still be necessary even when you use SSH keys for regular access.

When creating users, keep in mind that logging in with a password is disabled by default (`lock_passwd: true`), and that the newly created users do not have **`sudo`** rights.

The following examples show configurations for creating different users.

EXAMPLE 2: NEW USER WITH PASSWORD AND **sudo**

```
#cloud-config
users:
  - default
  - name: USER
    shell: /bin/bash
    groups: users
    # lock_passwd: Disable password login. Defaults to true
```

```
    lock_passwd: false
    passwd: HASH
    sudo: ALL=(ALL) NOPASSWD:ALL
```

EXAMPLE 3: NEW USER WITH SSH KEYS AND `sudo`

```
#cloud-config
users:
  - name: USER
    shell: /bin/bash
    groups: users
    ssh_import_id: None
    lock_passwd: true
    sudo: ALL=(ALL) NOPASSWD:ALL
    ssh_authorized_keys:
      - SSH_PUBLIC_KEY_1
      - SSH_PUBLIC_KEY_2
```

To connect and register with the SUSE Multi-Linux Manager, RMT or SUSEConnect, use `runcmd` to run the desired commands, for example:

EXAMPLE 4: SUSECONNECT CONFIGURATION

```
#cloud-config
runcmd:
  - SUSEConnect -r REGISTRATION_CODE -e EMAIL_ADDRESS
```

EXAMPLE 5: RMT CONFIGURATION

```
#cloud-config
runcmd:
 - curl --output rmt-client-setup http://RMT_SERVER/tools/rmt-client-setup
 - sh rmt-client-setup --host RMT_SERVER
     --regcert http://RMT_SERVER/rmt.crt
     --fingerprint FINGERPRINT --yes
```

Replace *`FINGERPRINT`* with the output of the following command that you run on your RMT server:

```
> sudo openssl x509 -noout -fingerprint -in /etc/rmt/ssl/rmt-ca.crt
```

For example: `0F:1F:2F:3F:4F:5F:6F:7F:8F:9F:AF:BF:CF:DF:EF:FF`.

For further information, see https://documentation.suse.com/sles-15/html/SLES-all/cha-rmt-client.html.

EXAMPLE 6: SUSE MULTI-LINUX MANAGER CONFIGURATION

```
#cloud-config
runcmd:
  - curl -SksO https://SERVER_HOSTNAME/pub/bootstrap/bootstrap.sh
  - /bin/bash bootstrap.sh
```

For further information, see https://documentation.suse.com/multi-linux-manager/en/docs/client-configuration/registration-bootstrap.html.

The following example shows a configuration that installs a package and starts a service during the first boot.

EXAMPLE 7: ADD *PACKAGE* AND START A SERVICE

```
#cloud-config
packages:
  - PACKAGE
runcmd:
  - systemctl enable SERVICE.service
  - systemctl start --no-block SERVICE.service
```

Note: Optional configuration files

You can optionally create other configuration files, called `meta-data`, `network-config` and `vendor-data`. For more information, see https://docs.cloud-init.io/en/latest/reference/data-sources/nocloud.html.

After you write the `user-data` file, provide the file to the virtual machine, as described in the following section.

6.2 Providing the user-data file to the virtual machine

Choose the method that matches your tooling.

6.2.1 Deploying with QEMU

There are two ways to deliver the configuration: on a seed image attached as a CD-ROM or from a Web server.

1. Make the configuration available to the virtual machine. Use either a seed image or a Web server:

   - **Seed image:** Create the seed image containing the `user-data` file:

     ```
     > mkisofs \
         -output seed.iso \
         -volid cidata -rational-rock -joliet \
         user-data
     ```

   - **Web server:** Copy the configuration file into a directory served by a Web server, for example, `/srv/www/htdocs/cloud-init/`, served at `http://www.example.com/cloud-init/`.

2. Start the virtual machine.

   ```
   > qemu-system-ARCH \
       -enable-kvm \
       -cpu host \
       -m 1G \
       -smp 1 \
       -drive if=virtio,format=qcow2,file=IMAGE.qcow2 \
       -nographic \
       -netdev user,id=net0,hostfwd=tcp::2222-:22 \
       -device virtio-net,netdev=net0 \
       DATA_SOURCE_OPTION
   ```

   Replace *`DATA_SOURCE_OPTION`* based on the chosen method from the previous step:

   - If you use seed image data source:

     ```
     -drive file=seed.iso,media=cdrom
     ```

   - If you use Web server data source:

     ```
     -smbios 'type=1,serial=ds=nocloud-net;s=http://www.example.com/cloud-init/'
     ```

6.2.2 Deploying with `virt-install`

If you deploy with `libvirt`, **`virt-install`** can generate the data source for you:

```
> virt-install \
    --name VM_NAME \
    --memory 1024 \
    --vcpus 1 \
```

```
    --import \
    --disk IMAGE.qcow2,bus=virtio \
    --cloud-init user-data=./user-data \
    --osinfo detect=on,require=off
```

7 Post-deployment configuration

After successfully deploying and configuring your SLES Minimal VM, the system is running and ready for use. To ensure optimal security and localization, perform the following post-deployment tasks.

7.1 Registering the system

Registering your SLES Minimal VM links it to your SUSE subscription. If the system was not registered during first boot, register it manually.

```
> sudo SUSEConnect -r REGISTRATION_CODE -e EMAIL_ADDRESS
```

You can also register with RMT using the setup script. For more information, see Configuring clients with `rmt-client-setup` (https://documentation.suse.com/sles-15/html/SLES-all/cha-rmt-client.html#sec-rmt-client-clientsetupscript).

7.2 Installing system updates

After SLES Minimal VM is successfully installed and registered, it is highly recommended to install the latest available online updates:

```
> sudo zypper patch
```

7.3 Changing the system locale

By default, the SLES Minimal VM image includes only the `en_US` locale. To use a different system language, install and select your desired locale. The following example commands configure the system for the `de_DE` locale.

1. Add the desired locale and install the required translation packages:

   ```
   > sudo zypper addlocale de_DE
   ```

2. Set the new locale:

```
> localectl set-locale LANG=de_DE.UTF-8
```

You can list all available system locales by running **`localectl list-locales`**.

7.4 Removing setup packages

JeOS Firstboot and the packages it pulls in are only required for the initial configuration of the system. You can leave these packages on the system, or, when the system is fully configured and you do not intend to reconfigure it, you can safely remove the wizard together with the dependencies:

```
> sudo zypper remove -u jeos-firstboot
```

Note: Configuration tools are removed as well

The command removes JeOS Firstboot along with dependencies, including configuration tools such as `jeos-config` or `ssh-pairing`. If you still need any of these tools, keep JeOS Firstboot installed.

8 Legal Notice

Copyright© 2006– 2026 SUSE LLC and contributors. All rights reserved.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or (at your option) version 1.3; with the Invariant Section being this copyright notice and license. A copy of the license version 1.2 is included in the section entitled “GNU Free Documentation License”.

For SUSE trademarks, see https://www.suse.com/company/legal/. All other third-party trademarks are the property of their respective owners. Trademark symbols (®, ™ etc.) denote trademarks of SUSE and its affiliates. Asterisks (*) denote third-party trademarks.

All information found in this book has been compiled with utmost attention to detail. However, this does not guarantee complete accuracy. Neither SUSE LLC, its affiliates, the authors, nor the translators shall be held liable for possible errors or the consequences thereof.

A GNU Free Documentation License

Copyright (C) 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the

Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or non-commercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

D. Preserve all the copyright notices of the Document.

E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

H. Include an unaltered copy of this License.

I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.

N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.

O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See https://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

```
Copyright (c) YEAR YOUR NAME.
```

```
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
A copy of the license is included in the section entitled “GNU
Free Documentation License”.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.