SUSE AI Factory Release Notes

SUSE AI Factory Release Notes

Publication Date: 2026-11-20

https://documentation.suse.com

Contents

1 Release 2.4.0 1

1.1 What's new 1

1.2 Key fixes 2

1.3 Upgrade notes 2

1.4 Known issues and limitations 3

2 Release 2.3.1 4

2.1 Key improvements and fixes 4

2.2 Upgrade notes 5

3 Release 2.3.0 6

3.1 What's new 6

Blueprint customization 6 • Custom blueprint catalogs 7 • Custom chart repositories 7 • Repository verification and readiness 8 • Workload monitoring 8 • Air-gapped deployments 9 • Application catalog 9 • Packaging 9

3.2 Key fixes 9

3.3 Upgrade notes 10

3.4 Known issues and limitations 11

4 Release 2.2.0 13

4.1 What's new 13

Application catalog 13 • Air-gapped deployments 14 • Workload recovery 14 • Usability improvements 15 • Packaging 15

4.2 Key fixes 15

4.3 Upgrade notes 16

4.4 Known issues and limitations 17

5 Release 2.1.0 18

5.1 What's new 18

Application catalog 18 • Git-backed Rancher Prime catalogs and Rancher Prime API access 19 • Extension delivery and security 19 • Workload and blueprint management 20

5.2 Key fixes 20

5.3 Upgrade notes 21

6 Release 2.0.1 22

6.1 Key improvements and fixes 22

7 Release 2.0.0 23

7.1 What's new 23

Core features 23

7.2 Known issues and behaviors 25

Installation and deployment 25 • NVIDIA blueprints 25 • NVIDIA AI Library 26 • Blueprint customization 26 • Deprecations 26

A Copyright 27

B GNU Free Documentation License 28

B1 0. PREAMBLE 28

B2 1. APPLICABILITY AND DEFINITIONS 28

B3 2. VERBATIM COPYING 30

B4 3. COPYING IN QUANTITY 30

B5 4. MODIFICATIONS 31

B6 5. COMBINING DOCUMENTS 33

B7 6. COLLECTIONS OF DOCUMENTS 33

B8 7. AGGREGATION WITH INDEPENDENT WORKS 34

B9 8. TRANSLATION 34

B10 9. TERMINATION 34

B11 1. FUTURE REVISIONS OF THIS LICENSE 35

B12 ADDENDUM: How to use this License for your documents 35

1 Release 2.4.0

This release builds on the 2.3.x line with new partner blueprints, new SUSE AI applications in the catalog, and unique default namespaces for new installations, plus fixes for secret references on the **Settings** page, large Git-hosted charts and extension access checks.

1.1 What's new

- **New partner blueprints**: The SUSE partner blueprint catalog now includes blueprints from three partners: `AlchemiStudio + vLLM` (Zentience Labs), `Tensormesh Platform on SUSE AI (vLLM)` (Tensormesh), and `Traefik Hub AI and MCP Gateway Installer` and `Traefik Hub AI and MCP Governance Demo` (Traefik Labs). Support for each blueprint is provided by its partner. Large partner charts such as AlchemiStudio now install from Git chart repositories #348 (https://github.com/SUSE/aif/pull/348).

- **New SUSE AI applications**: `vLLM Production Stack`, which supersedes the existing vLLM application, plus `Slurm Operator` and `Slurm Bridge` for running Slurm alongside Kubernetes #357 (https://github.com/SUSE/aif/pull/357).

- **NVIDIA catalog refresh**: The weekly NVIDIA AI Enterprise catalog refreshes are included. `DOCA Weave Service` (`dpf-weave`) is added to the NVIDIA AI Library #335 (https://github.com/SUSE/aif/pull/335), #350 (https://github.com/SUSE/aif/pull/350), #358 (https://github.com/SUSE/aif/pull/358).

- **Random default namespace for new installations**: The application and blueprint installation wizards now suggest a namespace with a random suffix, such as `coredns-k3x9q2a`, instead of `coredns-system`. Each new installation gets its own namespace, so installing the same application twice no longer fails because a deployment with the same name already exists in the shared namespace. You can still change the namespace, and existing installations keep theirs #338 (https://github.com/SUSE/aif/pull/338).

- **Incomplete secret references are caught before saving**: *Apply* on the **Settings** page is now blocked when a secret field has a secret selected but no key. The message names each such field and opens its section. The operator API rejects these partial references with HTTP `400`, and the CRDs reject them from any client #349 (https://github.com/SUSE/aif/pull/349).

1.2 Key fixes

- Setting the SUSE Application Collection, SUSE Registry or NVIDIA credentials, or the Rancher Prime catalog token and CA certificate secrets, to `None` now saves. Previously, the page reloaded with the old credentials filled in, or saving failed with errors such as `spec.applicationCollection.tokenSecretRef.name: Required value`. This also happened when the reference was set by Helm values or discovered by the operator #349 (https://github.com/SUSE/aif/pull/349).
- Clearing every field of a section on the **Settings** page no longer fails with `spec.rancherCatalog in body must be of type object` #349 (https://github.com/SUSE/aif/pull/349).
- Secret fields of custom repositories no longer silently drop a secret that has no key. Previously, saving appeared to succeed but stored `None` #349 (https://github.com/SUSE/aif/pull/349).
- Charts from Git chart repositories that are larger than 1 MiB unpacked now install. Previously, they failed with `ChartTooLarge` or `etcdserver: request is too large`. Chart files are now stored compressed, so a 2 MB chart takes about 0.43 MB #348 (https://github.com/SUSE/aif/pull/348).
- Global administrators are no longer refused access to the UI extension on their first navigation, for example, right after creating a cluster, with the message `Access check failed`. The extension now waits up to 30 seconds for Rancher Prime to load its management data before checking access, and a failed check is retried on the next navigation #302 (https://github.com/SUSE/aif/pull/302).

1.3 Upgrade notes

- **Updated `Settings` and `InstallAIExtension` CRDs**: The `name` and `key` of secret references must not be empty, and the `fleet`, `applicationCollection`, `suseRegistry`, `nvidia`, `appCatalog` and `rancherCatalog` sections of `Settings` accept `null`. The CRD hook job of the chart applies the CRDs on upgrade #349 (https://github.com/SUSE/aif/pull/349).
- **Existing partial secret references**: On Kubernetes 1.30 and later, a `Settings` resource that already stores a secret reference without a key, or a key without a secret, can still be updated as long as that field is not changed. Complete or clear these references the next time you edit the settings #349 (https://github.com/SUSE/aif/pull/349).

- **Use matching operator and UI extension versions**: The fixes for `None` and partial secret references change both the operator API and the **Settings** page, and require both the 2.4.0 operator and the 2.4.0 UI extension #349 (https://github.com/SUSE/aif/pull/349).
- **New default namespace pattern**: New installations get a `<APP>-<RANDOM>` namespace instead of `<APP>-system`. If your scripts or policies expect `<APP>-system`, set the namespace explicitly in the installation wizard. The *Manage* action still finds instances installed in the earlier `<APP>-system` namespace #338 (https://github.com/SUSE/aif/pull/338).

1.4 Known issues and limitations

- Charts from Git chart repositories are limited to a 4 MiB archive, 32 MiB unpacked and 1 MiB of compressed files in the Fleet `Bundle`.
- Non-administrator users get access to the UI extension through a `cluster-owner` role binding for their user on the `local` cluster. Users who are cluster owners only through a group, for example, an LDAP group or a GitHub organization, are refused access.
- The vLLM application is superseded by `vLLM Production Stack` and will be deprecated in a future release.

Full Changelog: aif-operator-2.3.1...aif-operator-2.4.0 (https://github.com/SUSE/aif/compare/aif-operator-2.3.1...aif-operator-2.4.0)

2 Release 2.3.1

This is the 2.3.1 release of SUSE AI Factory, bringing comprehensive AI workload management capabilities to Rancher Prime.

2.1 Key improvements and fixes

- Added a default SUSE partner blueprint catalog, controlled by the `partnerBlueprints` Helm value and enabled by default. Catalogs declared through Helm are now read-only on the **Settings** page and in the operator API, and are marked `Managed by Helm` #322 (https://github.com/SUSE/aif/pull/322).
- Added a `Community` blueprint source. Older operators reject blueprints that use `source: Community` #324 (https://github.com/SUSE/aif/pull/324).
- The Rancher Prime `Extensions` page now shows the logo and title of the SUSE AI Factory extension instead of a `Third-Party` card. The operator installs the extension the same way Rancher Prime does, and the logo is served from inside the cluster, so it also loads in air-gapped installations #325 (https://github.com/SUSE/aif/pull/325).
- Hardened the installation and cleanup of the UI extension. The operator refuses an extension that has the same name as its server release, and the finalizer only deletes a release that its own resource installed #325 (https://github.com/SUSE/aif/pull/325).
- Fixed workloads stuck in `Degraded` on clusters whose Fleet name differs from the Rancher Prime cluster ID. The installation wizards now show cluster display names instead of `c-m-…` IDs #330 (https://github.com/SUSE/aif/pull/330).
- Fixed the verification panel on the **Settings** page hiding the NGC chart access results when no NVIDIA mirror is set #321 (https://github.com/SUSE/aif/pull/321).
- The weekly NVIDIA AI Enterprise catalog refresh no longer removes applications that lose NVIDIA AI Enterprise support. It only removes their `Supported` label. Each refresh also produces a report of what changed #309 (https://github.com/SUSE/aif/pull/309), #323 (https://github.com/SUSE/aif/pull/323).

2.2 Upgrade notes

- **Partner blueprint catalog in air-gapped installations**: The partner catalog is synchronized from GitHub. In air-gapped installations, disable it with `partnerBlueprints.enabled=false` or point it at an internal mirror #322 (https://github.com/SUSE/aif/pull/322).
- **Duplicate partner catalogs**: If you added a catalog on the **Settings** page that points to the SUSE partner-blueprints repository, remove it after upgrading. Otherwise, two Fleet `GitRepo` resources synchronize the same blueprints and conflict #322 (https://github.com/SUSE/aif/pull/322).
- **Server-side apply for Helm-declared catalogs**: Keeping catalogs added on the **Settings** page next to catalogs declared in `blueprintCatalogs` requires server-side apply. Releases first installed with Helm 3 keep using client-side apply until you run one `helm upgrade --server-side=true` #322 (https://github.com/SUSE/aif/pull/322).
- `Community` **blueprint source**: SUSE AI Factory Operator 2.3.0 and earlier reject blueprints with the `Community` source. Do not use it until 2.3.1 is the minimum operator version in your environment #324 (https://github.com/SUSE/aif/pull/324).

Full Changelog: aif-operator-2.3.0...aif-operator-2.3.1 (https://github.com/SUSE/aif/compare/aif-operator-2.3.0...aif-operator-2.3.1)

3 Release 2.3.0

This release builds on the 2.2.x line with customizable blueprint deployments, custom chart repositories and Git-sourced blueprint catalogs, clearer repository and workload health reporting, and a new workload details view, plus several stability and installation improvements.

3.1 What's new

3.1.1 Blueprint customization

- **Customize blueprint deployments**: A new `Configuration` step in the blueprint installation and management wizard lets you override Helm values and enable or disable individual blueprint components before deployment. Disabled components are left out of the deployment and removed from the cluster. Blueprint workloads can be reconfigured later with the *Manage* action #265 (https://github.com/SUSE/aif/pull/265).

- **Configuration drift tracking**: Workloads report whether their configuration differs from the blueprint defaults, and the `Workloads` page shows a `Customized` badge next to the blueprint source. Only the values you changed are saved, not the full set of component values #287 (https://github.com/SUSE/aif/pull/287).

- **Partner icons and `Partner` source**: Blueprints accept an optional `icon`, either an `https://` URL or a base64-encoded raster `data:` URI of up to 16 KB, which is shown next to the source badge, and a new `Partner` source value. Updating a blueprint with an invalid specification now returns HTTP `422` instead of `500` #292 (https://github.com/SUSE/aif/pull/292).

3.1.2 Custom blueprint catalogs

- **Git-sourced blueprint catalogs**: Administrators can add external Git repositories that contain blueprint definitions in the `Custom Catalogs` section of **Settings** or through the `blueprintCatalogs` Helm value. The operator synchronizes each catalog into the cluster through its own Fleet `GitRepo` resource, with its own credential and CA certificate secrets #281 (https://github.com/SUSE/aif/pull/281).
- **New `BlueprintCatalog` CRD**: A cluster-scoped resource that describes a curated, branded collection of blueprints #281 (https://github.com/SUSE/aif/pull/281).
- **Browse blueprints by catalog**: The `Blueprints` page provides a catalog filter. Blueprints bundled with the chart are listed under `SUSE Blueprints` #281 (https://github.com/SUSE/aif/pull/281).

3.1.3 Custom chart repositories

- **Manage chart repositories from Settings**: Administrators can add, edit and delete Helm (HTTP or HTTPS), OCI and Git chart repositories, including credentials, in the `Repositories` section of **Settings**. The operator creates a `ClusterRepo` resource with the same name for each repository, and its applications are listed in the application catalog under their own library #244 (https://github.com/SUSE/aif/pull/244).
- **Single-chart OCI repositories**: Repositories whose URL already ends with the chart name, for example `oci://ghcr.io/nvidia/openshell/helm-chart`, install correctly with both Helm and Fleet. Use this to add the NVIDIA OpenShell charts #244 (https://github.com/SUSE/aif/pull/244), #293 (https://github.com/SUSE/aif/pull/293).
- **Verify before saving**: Custom repositories can be tested for credentials, reachability and access to a sample chart from the same form #244 (https://github.com/SUSE/aif/pull/244).

3.1.4 Repository verification and readiness

- **Three-part connection test**: In **Settings**, *Test* reports the registry connection, access to a sample chart, and the readiness of the Rancher Prime chart repository as separate results, so a successful login alone is no longer reported as success. The result names the chart and version that were tested, and denied access, missing content, invalid indexes, TLS errors and timeouts each have their own explanation #242 (https://github.com/SUSE/aif/pull/242).

- **Repository failures shown across the UI**: The `Overview` page lists failing managed repositories with links to **Settings** and Rancher Prime. Applications from an unavailable repository remain visible but cannot be installed, and the installation wizard explains missing repository indexes instead of reporting `configmaps "" not found` #242 (https://github.com/SUSE/aif/pull/242).

- **Explicit refresh**: *Test* is read-only. A new *Refresh* action asks Rancher Prime to download the index of a saved repository again #242 (https://github.com/SUSE/aif/pull/242).

3.1.5 Workload monitoring

- **Workload details**: Selecting a workload name on the `Workloads` page opens a details panel with the source, deployment strategy, target namespace and clusters, blueprint components, per-cluster status messages, value overrides, and the underlying Fleet resources or Helm release #221 (https://github.com/SUSE/aif/pull/221), #303 (https://github.com/SUSE/aif/pull/303).

- **Accurate status for Helm workloads**: Application workloads deployed with Helm now derive their status from pod and controller readiness. A crash-looping or unschedulable pod reports `Degraded` with the reason, and a pod that is still starting reports `Pending` for as long as it needs. Previously, a workload was reported as `Running` as soon as its Helm release existed #260 (https://github.com/SUSE/aif/pull/260).

3.1.6 Air-gapped deployments

- **NVIDIA repository aliases preserved in mirror mode**: Switching to a private NVIDIA mirror keeps every repository alias derived from the catalog, such as `nvidia-runai` or `nim-nvidia`, so existing workloads can still be upgraded and redeployed #237 (https://github.com/SUSE/aif/pull/237).
- **Bundled catalog logos**: Logos for 81 SUSE AI charts are bundled with the UI extension, so application tiles show the correct logo in connected and air-gapped installations, including behind private mirrors #245 (https://github.com/SUSE/aif/pull/245).

3.1.7 Application catalog

- **NVIDIA catalog refresh**: The weekly NVIDIA AI Enterprise catalog refreshes are included. NGC applications that lost their NVIDIA AI Enterprise support label, including several NeMo microservices, two NIM embedding models and `dgxc-admission-controller`, remain in the catalog without the `Supported` label. The NVIDIA GPU Operator no longer has the `Supported` label #301 (https://github.com/SUSE/aif/pull/301).

3.1.8 Packaging

- **Rancher Prime readiness check**: A pre-install and pre-upgrade hook job waits until the required Fleet and Rancher Prime catalog CRDs and the `cattle-ui-plugin-system` namespace exist before the operator is installed, and retries on temporary API errors #277 (https://github.com/SUSE/aif/pull/277), #289 (https://github.com/SUSE/aif/pull/289).

3.2 Key fixes

- The UI extension no longer remains in the `Failed` state after the operator re-creates its `aif-ui-config` ConfigMap. The operator now takes Helm ownership of an existing ConfigMap instead of failing every installation and upgrade with an `invalid ownership metadata` error #218 (https://github.com/SUSE/aif/pull/218).
- Custom UI extension settings are retained after uninstalling. The `aif-ui-config` ConfigMap was previously deleted with the release, so custom operator connection and catalog settings were lost on reinstallation #218 (https://github.com/SUSE/aif/pull/218).

- Failing Helm workloads are no longer reported as `Running`. For example, a NIM pod that did not fit in GPU memory was reported as `Running` while it was crash-looping #260 (https://github.com/SUSE/aif/pull/260).
- Kubeflow, LiteLLM and Qdrant no longer fail on the first installation wizard screen when chart access is denied or the Rancher Prime repository is disconnected despite a successful registry login #242 (https://github.com/SUSE/aif/pull/242).
- Applications such as Ollama show their own logo instead of a generic icon when their metadata contains a logo URL #245 (https://github.com/SUSE/aif/pull/245).
- Switching to an NVIDIA mirror no longer breaks later upgrades of applications installed from NVIDIA team repositories #237 (https://github.com/SUSE/aif/pull/237).

3.3 Upgrade notes

- **Mirror the `kubectl` image for air-gapped installations**: The new Rancher Prime readiness hook job uses the `registry.suse.com/suse/kubectl:1.35` image, which you can configure with the `global.kubectl.image` values. The job waits until Rancher Prime is ready, limited only by the installer timeout, such as `helm --timeout` or the Fleet `helm.timeoutSeconds` value #277 (https://github.com/SUSE/aif/pull/277), #289 (https://github.com/SUSE/aif/pull/289).
- **New CRD and settings**: The `blueprintcatalogs.ai-factory.suse.com` CRD and the `blueprintCatalogs` and `customRepos` settings are added, and the `AIWorkload` and `Blueprint` CRDs are updated. The CRD hook job of the chart applies them on upgrade #281 (https://github.com/SUSE/aif/pull/281), #244 (https://github.com/SUSE/aif/pull/244), #265 (https://github.com/SUSE/aif/pull/265).
- **Use matching operator and UI extension versions**: Chart access checks, blueprint customization and partner icons require both the 2.3.0 operator and the 2.3.0 UI extension #242 (https://github.com/SUSE/aif/pull/242), #265 (https://github.com/SUSE/aif/pull/265), #292 (https://github.com/SUSE/aif/pull/292).
- **Helm workload status may change**: Application workloads that were previously reported as `Running` may now report `Pending` or `Degraded` if their pods are not ready #260 (https://github.com/SUSE/aif/pull/260).

- `aif-ui-config` **is retained on uninstall**: Uninstalling the UI extension now leaves the `aif-ui-config` ConfigMap in place. Delete it manually for a clean reinstallation #218 (https://github.com/SUSE/aif/pull/218).
- **Standalone installations of the UI extension chart**: Installing or upgrading the `aif-ui` chart with `helm` without the operator, over an existing `aif-ui-config` ConfigMap, requires the `--take-ownership` option, available in Helm 3.15 and later #218 (https://github.com/SUSE/aif/pull/218).
- **Reserved custom repository names**: Custom repositories cannot use the names of the built-in SUSE AI Factory repositories, the default Rancher Prime repositories, the NVIDIA team repositories, or a name already used by another `ClusterRepo` resource #244 (https://github.com/SUSE/aif/pull/244).
- `Partner` **blueprint source**: SUSE AI Factory Operator 2.2.0 rejects blueprints with the `Partner` source. Do not use it until 2.3.0 is the minimum operator version in your environment #292 (https://github.com/SUSE/aif/pull/292).

3.4 Known issues and limitations

- Air-gap support covers private chart repositories, private Git repositories, repository credentials and CA trust. Preparing the cluster remains a separate task: node and containerd registry mirrors, DNS, host proxies and operating system repositories are not configured by SUSE AI Factory.
- Container image references inside blueprint values are not rewritten. Your containerd registry mirrors must resolve them transparently.
- Git over SSH is not supported for blueprint input and GitOps output. Use HTTPS with credentials and, where required, a private CA certificate.
- Blueprint partner icons specified as `https://` URLs do not load in air-gapped installations. Use base64-encoded `data:` URIs instead.
- A custom HTTPS repository that uses a certificate issued by a private CA is not trusted through the CA bundle alone. As a workaround, enable `Skip TLS verification` for that repository.
- Anonymous connection tests against OCI registries that require repository-scoped tokens, such as GitHub Container Registry, report an authentication failure even though the charts can be pulled anonymously.

- Chart access is only checked for `https://` Helm and `oci://` repositories. A plain `http://` Helm repository can pass the connection test but reports a configuration error for chart access.
- Running chart access checks repeatedly against repositories with very large indexes can exceed the operator memory limit and restart the operator.
- The OpenShell gateway chart requires the Agent Sandbox CRDs and controller (`agents.x-k8s.io`) on the target cluster.
- A Helm workload whose pod is stuck for a reason that is only reported as a pod event, such as `FailedMount` for a missing secret or ConfigMap, remains `Pending` instead of `Degraded`.
- Upgrade, rollback and retry apply to blueprint workloads only. A workload that has never reached a healthy, fully rolled out state has no rollback target.

Full Changelog: aif-operator-2.2.0...aif-operator-2.3.0 (https://github.com/SUSE/aif/compare/aif-operator-2.2.0...aif-operator-2.3.0)

4 Release 2.2.0

This release builds on the 2.1.x line with enhanced support for air-gapped deployments, recovery operations for blueprint workloads, an NVIDIA AI Enterprise application catalog that is generated and refreshed automatically, and a range of reliability fixes in the operator's Helm lifecycle.

4.1 What's new

4.1.1 Application catalog

- **Generated NVIDIA AI Enterprise catalog**: The NVIDIA AI Library is generated from the NVIDIA GPU Cloud (NGC) catalog and gated on NVIDIA AI Enterprise support, replacing the previously hand-maintained label refresh #223 (https://github.com/SUSE/aif/pull/223).
- **Automated catalog refresh**: A scheduled job regenerates the catalog weekly, so the `Supported` labels on NVIDIA applications stay current between releases #232 (https://github.com/SUSE/aif/pull/232).
- **NGC repository classification**: NGC repository paths are classified as organization, public, gated or excluded. Gated repositories are provisioned with the authentication secret, and unrecognized paths fall back to anonymous access #223 (https://github.com/SUSE/aif/pull/223).
- **NGC image pull secret injection**: NVIDIA charts receive the `ngc-secret` image pull secret under both supported chart value conventions, which resolves `403` errors caused by an empty default suppressing the injection #223 (https://github.com/SUSE/aif/pull/223).
- **Catalog scoped to managed repositories**: The `Apps` page lists applications only from `ClusterRepo` resources that SUSE AI Factory created. Previously, an unrelated `ClusterRepo` could add applications to the SUSE AI or NVIDIA libraries #182 (https://github.com/SUSE/aif/pull/182).

4.1.2 Air-gapped deployments

- **Private chart and Git sources**: Blueprints reference a chart repository by its identity, while the registry endpoints in **Settings** determine where that repository is hosted. The same blueprints therefore deploy unchanged against a local mirror. Private HTTPS Git is supported for both blueprint input and GitOps output #224 (https://github.com/SUSE/aif/pull/224).
- **Private CA certificate propagation**: You can select a CA certificate secret for SUSE Application Collection, SUSE Registry and NVIDIA in **Settings**. The operator propagates it to Rancher Prime and Fleet, and handles CA certificate and credential rotation #200 (https://github.com/SUSE/aif/pull/200).
- **NVIDIA blueprint repository in mirrored mode**: Both the NVIDIA application and NVIDIA blueprint repository identities are preserved when mirrored and pointed at your private OCI URL, so NVIDIA blueprints continue to resolve #201 (https://github.com/SUSE/aif/pull/201).
- **Image registry override**: A single `global.imageRegistry` value redirects every image shipped by the operator and UI extension charts #209 (https://github.com/SUSE/aif/pull/209).

4.1.3 Workload recovery

- **Upgrade, roll back and retry**: Blueprint workloads can be upgraded to a new blueprint version, rolled back, or retried after a failed deployment directly from the UI. Application workloads do not support these operations #214 (https://github.com/SUSE/aif/pull/214).
- **Verified rollback target**: A blueprint version becomes a rollback target only after it has been fully rolled out across all target clusters, so a workload cannot be rolled back to a version that never reached a healthy state #214 (https://github.com/SUSE/aif/pull/214).
- **Per-component and per-pod status**: Workloads report their status for each component and pod, including while a deployment is failing, which makes it easier to identify the component that is blocking the rollout #214 (https://github.com/SUSE/aif/pull/214).

4.1.4 Usability improvements

- **Open workloads in Rancher Prime**: Each workload row provides an *Open in Rancher* action that opens the corresponding Helm release or namespace, with a cluster selector for multi-cluster workloads #206 (https://github.com/SUSE/aif/pull/206).
- **Library filter is preserved**: Cancelling an application installation returns you to the library you were browsing, and filtered catalog views can be bookmarked and shared #215 (https://github.com/SUSE/aif/pull/215).
- **Catalog metadata for the UI extension**: The extension is listed as SUSE AI Factory with the correct metadata in the Rancher Prime `Apps` and `Marketplace` views #230 (https://github.com/SUSE/aif/pull/230).
- **Clearer confirmation dialogs**: The upgrade and rollback confirmation dialogs explain the effect of the operation #229 (https://github.com/SUSE/aif/pull/229).

4.1.5 Packaging

- **CRD lifecycle**: CRDs are installed natively on first installation, and a hook job applies schema upgrades. The new `crds.rbac.create` and `crds.serviceAccountName` values support restricted environments where the installer cannot create cluster-scoped RBAC #202 (https://github.com/SUSE/aif/pull/202).
- **Per-component Helm release names**: Blueprint components accept an optional `releaseName` value that pins the Helm release name of a component. It defaults to the chart name #202 (https://github.com/SUSE/aif/pull/202).
- **UI extension installed by the operator**: The operator installs the UI extension itself, so `aif-ui` is no longer installed as a separate Helm chart #233 (https://github.com/SUSE/aif/pull/233).

4.2 Key fixes

- Restarting the operator no longer leaves the UI extension's Helm release in a `failed` state without recovering #199 (https://github.com/SUSE/aif/pull/199).
- The UI extension no longer remains on an incorrect version after consecutive upgrades and downgrades #177 (https://github.com/SUSE/aif/pull/177).

- Deleting an application workload now uninstalls the underlying Helm chart instead of leaving the release in the `Uninstalling` state with orphaned resources #193 (https://github.com/SUSE/aif/pull/193).
- The operator no longer downloads the UI extension chart on every reconcile, which previously caused continuous registry traffic and could exhaust public registry rate limits #185 (https://github.com/SUSE/aif/pull/185).
- Attaching image pull secrets no longer removes other service account fields, such as labels, annotations, owner references and finalizers #192 (https://github.com/SUSE/aif/pull/192).
- Several user interface strings and tooltips that previously displayed raw translation keys now render correctly #211 (https://github.com/SUSE/aif/pull/211).
- Long Helm release names no longer prevent the UI extension from installing. The generated service name could exceed the Kubernetes 63-character limit and be rejected #210 (https://github.com/SUSE/aif/pull/210).

4.3 Upgrade notes

- **CRDs are retained on uninstall**: `helm uninstall` no longer removes CRDs or the `Settings` resource. Bundled blueprints and the UI extension are still removed. Schema upgrades are applied by a pre-install and pre-upgrade hook job #202 (https://github.com/SUSE/aif/pull/202).
- **Mirror the `kubectl` image for air-gapped installations**, because the CRD hook job requires it. Alternatively, set `crds.manageWithJob=false` and apply the CRDs manually with `kubectl apply --server-side -f crds/` before each upgrade #202 (https://github.com/SUSE/aif/pull/202).
- **The UI extension is no longer installed separately**: If your automation installs the `aif-ui` chart as a separate step, remove that step and the `aiExtension.enabled: false` override #233 (https://github.com/SUSE/aif/pull/233).
- **Deleting workloads outside the UI requires a Rancher Prime token**: Deleting an `AIWorkload` resource with `kubectl` or through GitOps only uninstalls the chart when a token is configured in **Settings** > **Rancher API Access**. Without a token, the deletion is held rather than orphaning the Helm release #193 (https://github.com/SUSE/aif/pull/193).
- **Manually created chart repositories are ignored**: Only `ClusterRepo` resources created by SUSE AI Factory contribute to the application catalog #182 (https://github.com/SUSE/aif/pull/182).

- **HTTPS Git authentication**: The authentication type setting is deprecated, and existing configurations continue to work. For new authenticated HTTPS configurations, select a password or personal access token. The user name is optional unless the Git server requires an account name. SSH is not supported #224 (https://github.com/SUSE/aif/pull/224).
- **Unused settings were removed**: The SUSE Application Collection API endpoint, catalog discovery and image rewrite settings, and the **Advanced** section of **Settings** were removed #224 (https://github.com/SUSE/aif/pull/224).
- **New workload validation**: Review existing `AIWorkload` resources before upgrading. The deployment strategy is now immutable, blueprint workloads require at least one target cluster, and GitOps workloads cannot combine the local cluster with downstream clusters #214 (https://github.com/SUSE/aif/pull/214).
- **Image overrides for air-gapped installations**: The `global.imageRegistry` and `global.imagePullSecrets` values of the `aif-operator` chart are now forwarded to the managed `aif-ui` chart. Existing nested overrides take precedence #209 (https://github.com/SUSE/aif/pull/209).

4.4 Known issues and limitations

- Air-gap support covers private chart repositories, private Git repositories, repository credentials and CA trust. Preparing the cluster remains a separate task: node and containerd registry mirrors, DNS, host proxies and operating system repositories are not configured by SUSE AI Factory.
- Container image references inside blueprint values are not rewritten. Your containerd registry mirrors must resolve them transparently.
- Git over SSH is not supported. Use HTTPS with credentials and, where required, a private CA certificate.
- Upgrade, rollback and retry apply to blueprint workloads only. A workload that has never reached a healthy, fully rolled out state has no rollback target.

Full Changelog: aif-operator-2.1.0...aif-operator-2.2.0 (https://github.com/SUSE/aif/compare/aif-operator-2.1.0...aif-operator-2.2.0)

5 Release 2.1.0

This release builds on the 2.0.x line with an operator-served application catalog that is now the default, git-backed Rancher Prime catalog support, expanded NVIDIA integration, hardened extension chart delivery, and a range of workload/UI reliability fixes.

5.1 What's new

5.1.1 Application catalog

- **Operator-served catalog, now the default**: The operator serves the application catalog through a static catalog configuration and a CRD lifecycle job, and the UI now loads applications from this bundled catalog by default (`useStaticCatalog=true`). Runtime discovery from live chart repositories remains available by setting the flag to `false` #145 (https://github.com/SUSE/aif/pull/145), #172 (https://github.com/SUSE/aif/pull/172).
- **NVIDIA AI Enterprise library**: The NVIDIA AI Library is populated with NVIDIA AI Enterprise-supported Helm charts, and the default catalog ships the org-level NVIDIA repositories out of the box #155 (https://github.com/SUSE/aif/pull/155), #172 (https://github.com/SUSE/aif/pull/172).
- **Application sorting and support labels**: The `Apps` page sorts supported applications first (default) or by name, shows NVIDIA support status through labels, and defaults the library filter to all libraries. The sort control is shared across the `Apps`, `Blueprints`, and `Workloads` screens #155 (https://github.com/SUSE/aif/pull/155), #172 (https://github.com/SUSE/aif/pull/172).
- **NGC team repositories**: The operator supports NVIDIA NGC team repositories with gated authentication. The default catalog currently ships only the org-level NVIDIA repositories, so team-repository provisioning is dormant until the catalog expands #163 (https://github.com/SUSE/aif/pull/163).

5.1.2 Git-backed Rancher Prime catalogs and Rancher Prime API access

- **Git-backed `ClusterRepo` support**: Blueprint components and application workloads can now be deployed from git-backed Rancher Prime `ClusterRepo` resources (`spec.gitRepo`/`spec.gitBranch`), including the built-in `rancher-charts` and `rancher-ui-plugins` repositories, which previously failed. The operator fetches the chart from the Rancher Prime catalog API on the management cluster and ships it as an embedded Fleet `Bundle`, so air-gapped downstream clusters deploy without each cluster needing to reach Rancher Prime or hold an API token. Identical reconciles are skipped through a chart fingerprint #156 (https://github.com/SUSE/aif/pull/156).

- **{*ranchera}** API access settings*: A new **Settings > Rancher API Access** section manages the Rancher Prime catalog credential end to end. Selecting *Authorize* mints a Rancher Prime API token as the signed-in user, *Test* validates a token before saving, and the section shows the granted expiry and warns before it lapses. When the token expires, select *Authorize* again to renew it. The Rancher Prime CA certificate is discovered automatically when none is configured, so TLS verification stays enabled by default. The configuration is hot-reloaded without an operator restart #156 (https://github.com/SUSE/aif/pull/156).

- **Oversized git charts fail fast**: Charts whose unpacked Fleet `Bundle` would exceed the Kubernetes object-size limit fail terminally with `ChartTooLarge` and guidance to host them in an OCI or HTTP `ClusterRepo` instead, rather than retrying indefinitely #156 (https://github.com/SUSE/aif/pull/156).

5.1.3 Extension delivery and security

- **Authenticated and TLS registries**: `InstallAIExtension` can pull the UI extension chart from authenticated and TLS-enabled registries. The `aif-operator` Helm chart exposes the corresponding Helm authentication and TLS settings for the bundled extension #162 (https://github.com/SUSE/aif/pull/162).

- **Registry hardening**: A registry-host allowlist guards against confused-deputy requests (with a start-up warning when the allowlist is empty), insecure registry TLS is gated behind two explicit opt-ins, plain-HTTP OCI chart pulls are no longer performed, and `https+tls` chart URLs that are not a direct `.tgz` are rejected. Terminal reconcile failures now correctly set `Ready=False` #162 (https://github.com/SUSE/aif/pull/162).

5.1.4 Workload and blueprint management

- **Pre-flight credential checks**: Blueprint credentials are validated before installation, so missing credentials are reported up front instead of surfacing as a failed deployment #148 (https://github.com/SUSE/aif/pull/148).
- **Clearer failure reporting**: Workload failure reasons are shown on the `AI Workloads` list, and `ClusterRepo` resolution failures are surfaced on the `AIWorkload` status #148 (https://github.com/SUSE/aif/pull/148).
- **Protected bundled blueprints**: Deletion of bundled blueprints is rejected by the API, and the delete action is hidden for them in the UI #122 (https://github.com/SUSE/aif/pull/122).
- **Updated blueprint**: The `simple-chatbot-with-rag` blueprint is updated to version 1.0.2. The default model changes from `gemma:2b` to `qwen2.5:3b` (larger context window); `qwen2.5:3b` is provided for research use only under the Qwen Research License #154 (https://github.com/SUSE/aif/pull/154).

5.2 Key fixes

- Rancher Prime and operator index caches are refreshed when the extension version changes, self-healing a stale index cache after an extension upgrade #152 (https://github.com/SUSE/aif/pull/152).
- `InstallAIExtension` status is patched to avoid `resourceVersion` conflicts #140 (https://github.com/SUSE/aif/pull/140).
- The family label is preserved when saving an edited blueprint as a new version #139 (https://github.com/SUSE/aif/pull/139).
- Pull-secret namespaces are no longer created on the management cluster for downstream-only workloads #130 (https://github.com/SUSE/aif/pull/130).
- The UI clarifies that the blueprint installation namespace is only a default #141 (https://github.com/SUSE/aif/pull/141).
- Deployment type cards are aligned to equal height #129 (https://github.com/SUSE/aif/pull/129).

5.3 Upgrade notes

- **CRD lifecycle on upgrade**: The operator chart applies and upgrades its custom resource definitions (CRDs) through a pre-upgrade job (`crds.manageWithJob=true`), which only creates or updates CRDs and never deletes them. In restricted environments where the job cannot run, set `crds.manageWithJob=false` and apply the CRDs from the chart's `crds/` directory manually before upgrading #145 (https://github.com/SUSE/aif/pull/145).
- **Git-backed catalogs require a Rancher Prime token**: To deploy from git-backed `ClusterRepo` resources, authorize a Rancher Prime API token under **Settings** > **Rancher API Access** after upgrading. Charts too large to ship as a Fleet `Bundle` fail with `ChartTooLarge`; host those in an OCI or HTTP `ClusterRepo` instead #156 (https://github.com/SUSE/aif/pull/156).
- **Chatbot default model change**: After upgrading `simple-chatbot-with-rag` to 1.0.2, new chats default to `qwen2.5:3b` (`gemma:2b` is removed); existing chats remain readable #154 (https://github.com/SUSE/aif/pull/154).

Full Changelog: aif-operator-2.0.1...aif-operator-2.1.0 (https://github.com/SUSE/aif/compare/aif-operator-2.0.1...aif-operator-2.1.0)

6 Release 2.0.1

This is the 2.0.1 release of SUSE AI Factory, bringing comprehensive AI workload management capabilities to Rancher Prime.

6.1 Key improvements and fixes

- Fixed pull secrets not being delivered to certain downstream clusters, which left workloads stuck in ImagePullBackOff. The pull-secret bundle now targets the downstream cluster by the `management.cattle.io/cluster-name` label instead of clusterName #107 (https://github.com/SUSE/aif/pull/107).
- Published `simple-chatbot-with-rag` and `simple-chatbot-with-rag-vllm` 1.0.1 with updated image revisions (#132 (https://github.com/SUSE/aif/pull/132)):
  - `open-webui`: 0.6.41-14.20 to 0.6.41-15.2
  - `vllm-openai`: 0.19.0 to 0.19.0-5.29
- Reduced resource requests for the Phi-3-mini-4k-instruct model.
- Marked the 1.0.0 simple-chatbot-with-rag, simple-chatbot-with-rag-vllm, and suse-inference-endpoint blueprints as deprecated as their 1.0.0 have blocking issues.

Full Changelog: aif-operator-2.0.0...aif-operator-2.0.1 (https://github.com/SUSE/aif/compare/aif-operator-2.0.0...aif-operator-2.0.1)

7 Release 2.0.0

This is the **first official release** of SUSE AI Factory, bringing comprehensive AI workload management capabilities to Rancher Prime.

SUSE AI Factory is a Rancher Prime UI Extension for managing AI workloads and applications across Kubernetes clusters. This extension provides a unified interface for installing, managing and monitoring AI applications in Rancher Prime-managed clusters.



Note

This extension requires an active SUSE AI Factory (https://www.suse.com/products/ai/) subscription to access the application catalog.

7.1 What's new

7.1.1 Core features

7.1.1.1 AI workload management

- **Multi-cluster AI workload deployment**: Deploy and manage AI applications across multiple Rancher Prime-managed Kubernetes clusters from a single interface
- **Blueprint-based application templates**: Preconfigured application blueprints for common AI use cases:
  - Simple Chatbot with RAG (Retrieval-Augmented Generation)
  - Simple Chatbot with RAG using vLLM
  - NVIDIA RAG Minimal deployment
  - SUSE Inference Endpoint

- **Declarative workload definition**: Kubernetes-native Custom Resource Definitions (CRDs) for AI workloads, blueprints, and settings
- **GitOps integration**: Fleet-based GitOps workflow support for managing AI workload configurations

7.1.1.2 User interface

- **Unified dashboard**: Overview page with at-a-glance statistics and recent activity
- **Application catalog**: Browse and install AI applications from SUSE AI Factory and NVIDIA AI Library
- **Multi-step installation wizard**: Guided workflows for deploying applications and blueprints
- **Application instance management**: Monitor and manage deployed AI workloads and their metrics
- **Blueprint management**: Create, edit, and manage custom blueprints
- **Settings management**: Helm and Git repositories configuration

7.1.1.3 Operator and backend

- **SUSE AI operator**: Kubernetes operator managing the lifecycle of AI extensions and workloads
- **Custom resource definitions**:
  - `AIWorkload`: Defines AI application instances
  - `Blueprint`: Defines reusable application templates
  - `InstallAIExtension`: Manages UI extension installation
  - `Settings`: Centralized configuration management
- **Multiple deployment strategies**: Helm for simple deployments to local clusters, Fleet integration for GitOps for downstream and multi-cluster deployments
- **Multi-vendor support**: Seamless integration with both SUSE and NVIDIA AI components
- **Credential management**: Automatic injection of registry credentials and pull secrets

7.1.1.4 Integration and connectivity

- **SUSE application collection integration**: Access to curated AI application catalog
- **NVIDIA NGC integration**: Direct access to NVIDIA AI applications and models
- **Fleet integration**: GitOps-based deployment workflows
- **Multi-cluster support**: Deploy to local and downstream Rancher Prime clusters

7.2 Known issues and behaviors

7.2.1 Installation and deployment

- Fleet must be installed before deploying the AIF operator, the installation of the AIF operator may fail.
- Standalone UI extension installation through Rancher Prime Extensions interface is not supported. Use the AIF operator default values to install it.
- Images are distributed via GitHub Container Registry (ghcr.io). In the following releases, images will be distributed via the SUSE Registry.

7.2.2 NVIDIA blueprints

- **RAG v2.5.1+**: rag-server image version 2.5.1 does not exist in the registry. See #618 (https://github.com/NVIDIA-AI-Blueprints/rag/issues/618).
- **RAG v2.5.0+**: nv-ingest deployment renders duplicate `OTEL_EXPORTER_OTLP_ENDPOINT` environment variable, causing Fleet/ArgoCD deployments to fail. See #687 (https://github.com/NVIDIA-AI-Blueprints/rag/issues/687).
- **RAG v2.6.0**: NIM embedding and reranking charts do not pass `model.profiles` to NIMCache, causing all profiles (~11) to download instead of the selected one. See #681 (https://github.com/NVIDIA-AI-Blueprints/rag/issues/681).
- **RAG v2.5.1+**: Service names use hardcoded `nvidia-blueprint-rag` prefix and ignore `nameOverride`/`fullnameOverride` values. See #662 (https://github.com/NVIDIA-AI-Blueprints/rag/issues/662).

- **RAG v2.6.0**: **Critical** - NIMs cannot be deployed in air-gapped environments; chart missing `spec.storage.pvc.name` field to use existing PVC. See #693 (https://github.com/NVIDIA-AI-Blueprints/rag/issues/693).
- **AIQ v2.1.0**: Chart hardcodes `ns-aiq` namespace, ignoring release namespace; incompatible with Fleet/ArgoCD. See #290 (https://github.com/NVIDIA-AI-Blueprints/aiq/issues/290).
- **AIQ v2.1.0+**: Local inference configuration requires manual ConfigMap creation; not documented or exposed via Helm values. See #302 (https://github.com/NVIDIA-AI-Blueprints/aiq/issues/302).

7.2.3 NVIDIA AI Library

- Not all NVIDIA Helm charts in the catalog are NVIDIA AI Enterprise supported; verify support status at the NGC Helm catalog (https://catalog.ngc.nvidia.com/search?resourceType=helm_chart&label=NVIDIA+AI+Enterprise+Supported).

7.2.4 Blueprint customization

- Bundled blueprints cannot be modified directly during the deployment. Users must create a copy to customize configuration or component versions.

7.2.5 Deprecations

SUSE AI Deployer and SUSE AI Lifecycle Manager are now superseded by SUSE AI Factory. Update as soon as possible.

A Copyright

Copyright © 2026–2026-11-20 SUSE LLC and contributors. All rights reserved.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or (at your option) version 1.3; with the Invariant section being this copyright notice and license. A copy of the license version 1.2 is included in the section entitled 'GNU Free Documentation License'.

For SUSE trademarks, see https://www.suse.com/company/legal/. All third-party trademarks are the property of their respective owners. Trademark symbols (®, ™ etc.) denote trademarks of SUSE and its affiliates. Asterisks (*) denote third-party trademarks.

All information found in this book has been compiled with utmost attention to detail. However, this does not guarantee complete accuracy. Neither SUSE LLC, its affiliates, the authors nor the translators shall be held liable for possible errors or the consequences thereof.

B GNU Free Documentation License

Copyright © 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

B1 0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

B2 1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

B3 2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or non-commercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

B4 3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document’s license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

B5 4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

1. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
2. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
3. State on the Title page the name of the publisher of the Modified Version, as the publisher.
4. Preserve all the copyright notices of the Document.
5. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
6. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
7. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document’s license notice.

8. Include an unaltered copy of this License.

9. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

10. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

11. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

12. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

13. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.

14. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.

15. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any

one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

B6 5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

B7 6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

B8 7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

B9 8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

B10 9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

B11 1. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See https://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

B12 ADDENDUM: How to use this License for your documents

```
Copyright (c) YEAR YOUR NAME.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
A copy of the license is included in the section entitled "GNU
Free Documentation License".
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with…Texts."" line with this:

```
with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.